

Connectors 88318.3000



Technical data

Minimum wood dimensions with screws Ø5x60mm on the secondary beam	100 x 200 mm
VPE	4
Connector height	180 mm
Connector thickness (assembled)	18 mm
Connector width, main beam section	110 mm
Connector width, secondary beam section	80 mm
Number of concrete anchors for main beam section	4
Screws for secondary beam section	17 St. Ø5 x 60 - 120 mm

Concrete connection: Equally sturdy and simple HVP connection to concrete or steel up to about 300 kN. An anchor plate with concrete anchors ensures that the forces are applied properly into the concrete element. The secondary joist connection is realised with a normal HVP connector part.

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .

Connectors 88318.3000

Static values

Geometrie [mm]			Ø Bohrung [mm]	Anzahl Anker/Schraube	Ankertyp	Bauteildicke [mm]	Bemessungswert der Einwirkung in Einschubrichtung [kN]				Schraube 8.8	Injektionsbohrung
B	H	D					F2,Rd, Beton		F2,Rd, Stahl			
110	180	15	13	4	FBS II 10x100 45,35,15 SK	140	54,3		129,5		M12	Nein
					FH II 12/15 SK	120		48,8				Nein
					MMS-Plus F 12x120/30	150	58,4					Nein

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .

Connectors 88318.3000

Accessoires



50934.2000
Grooving cutter Ø 20 mm



58396.0000
Collet holder




58396.0012
Collet Ø 12 mm



99111.5060
Countersunk screws V2A
5 x 60 mm



99111.5070
Countersunk screw V2A 5
x 70 mm



99810.0100
Countersunk concrete
screw 10 x 100 mm



99812.0090
high-performance anchor
12 x 90 mm



99818.0125
Female-threaded anchor
18 x 125 mm Female
thread: M 12

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .