

Connectors 88435.2000



Technical data

Dimensions W x H x D (mm)	240 x 350 x 20
Number of screws	52
Usable screw size	Ø8 x 100 - 240 mm
VPE	4

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .

Connectors 88435.2000

Static values

Effektive Gewindelänge (l_{ef})		Mindestquerschnitt (mm)				Charakteristische Tragfähigkeit R_k (kN)				
						Brettschichtholz GL24h ($\rho_k = 385 \text{ kg/m}^3$)				
		HT		NT		NT		HT		
Schrauben	l_{ef} (mm)	Höhe	Breite	Höhe	Breite	$F_{2,Rk}$	$F_{3,Rk}$	$F_{4,Rk}$	$F_{4,Rk}$	$F_{1,Rk}$
8x160 mm	150 mm	370	160	370	260	251,44	36,40	88,00	139,14	78,23
8x180 mm	170 mm	400	180	400	260	281,42	36,40	88,00	139,14	87,56
8x200 mm	190 mm	430	200	430	260	311,05	36,40	88,00	139,14	96,78
8x220 mm	210 mm	460	220	460	260	340,37	36,40	88,00	139,14	105,90
8x240 mm	230 mm	490	240	490	260	363,62	36,40	88,00	139,14	113,13

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .

Connectors 88435.2000

Accessoires



50934.2000
Grooving cutter Ø 20 mm




58396.0000
Collet holder



58396.0012
Collet Ø 12 mm



99211.0812
Countersunk screw 8 x
120 mm



99211.0818
Countersunk screw 8 x
180 mm

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .