

Connectors 88425.1000



Technical data

Dimensions W x H x D (mm)	120 x 250 x 20
Number of screws	20
Usable screw size	Ø8 x 100 - 240 mm
Characteristic load-bearing capacity* in the insertion direction with screws Ø8x160mm	75,43 kN
Minimum timber dimensions with screws Ø8x160mm on the main beam	160 x 270 mm
Characteristic load-bearing capacity* in the insertion direction with screws Ø8x240mm	109,09 kN
Minimum timber dimensions with screws Ø8x160mm on the secondary beam	140 x 270 mm
VPE	4

The new disposed inclined drilled holes as well as the possibility of using different screws lengths guarantee the adaptability to the small timber cross-sections too.

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .

Connectors 88425.1000

Static values

Effektive Gewindelänge ($\varnothing_{ef}$)		Mindestquerschnitt (mm)				Charakteristische Tragfähigkeit Rk (kN)				
						Brettschichtholz GL24h ($\varnothing_k = 385 \text{ kg/m}^3$)				
		HT		NT		NT		HT		
Schrauben	$\varnothing_{ef}$ (mm)	Höhe	Breite	Höhe	Breite	$F_{2,Rk}$	$F_{3,Rk}$	$F_{4,Rk}$	$F_{4,Rk}$	$F_{1,Rk}$
8x160 mm	150 mm	270	160	270	140	75,43	33,85	33,85	53,52	52,15
8x180 mm	170 mm	300	180	300	140	84,43	33,85	33,85	53,52	58,37
8x200 mm	190 mm	330	200	330	140	93,31	33,85	33,85	53,52	64,52
8x220 mm	210 mm	360	220	360	140	102,11	33,85	33,85	53,52	70,60
8x240 mm	230 mm	390	240	390	140	109,09	33,85	33,85	53,52	75,42

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .

Connectors 88425.1000

Accessoires



50934.2000
Grooving cutter Ø 20 mm



58396.0000
Collet holder




58396.0012
Collet Ø 12 mm



58400.0000
Milling and assembly
template for connectors
88420 - 88560



99211.0812
Countersunk screw 8 x
120 mm



99211.0818
Countersunk screw 8 x
180 mm

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .