

Connectors 88555.1000



Technical data	
Dimensions W x H x D (mm)	140 x 550 x 20
Number of screws	56
Usable screw size	Ø8 x 100 - 240 mm
Characteristic load-bearing capacity* in the insertion direction with screws Ø8x160mm	301,73 kN
Minimum timber dimensions with screws Ø8x160mm on the main beam	170 x 570 mm
Characteristic load-bearing capacity* in the insertion direction with screws Ø8x240mm	436,34 kN
Minimum timber dimensions with screws Ø8x160mm on the secondary beam	160 x 570 mm
VPE	4

The heavy-duty HVP of the series 885 with a width of 140 mm are optimally suitable for wide beams (from 170 mm) under very high loads. A further quality criterion of the Pitzl HVP connectors series is the anodisation. Beside a smooth-running assembly and a dirty-free surface it provides the Pitzl HVP a very beautiful look.

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .

Connectors 88555.1000

Static values

Effektive Gewindelänge ($\varnothing_{ef}$)		Mindestquerschnitt (mm)				Charakteristische Tragfähigkeit Rk (kN)				
						Brettschichtholz GL24h ($\varnothing_k = 385 \text{ kg/m}^3$)				
		HT		NT		NT		HT		
Schrauben	$\varnothing_{ef}$ (mm)	Höhe	Breite	Höhe	Breite	$F_{2,Rk}$	$F_{3,Rk}$	$F_{4,Rk}$	$F_{4,Rk}$	$F_{1,Rk}$
8x160 mm	150 mm	570	160	570	160	301,73	36,40	94,77	149,84	52,15
8x180 mm	170 mm	600	180	600	160	337,70	36,40	94,77	149,84	58,37
8x200 mm	190 mm	630	200	630	160	373,26	36,40	94,77	149,84	64,52
8x220 mm	210 mm	660	220	660	160	408,44	36,40	94,77	149,84	70,60
8x240 mm	230 mm	690	240	690	160	436,34	36,40	94,77	149,84	75,42

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .

Connectors 88555.1000

Accessoires



50934.2000
Grooving cutter Ø 20 mm




58396.0000
Collet holder



58396.0012
Collet Ø 12 mm



99211.0812
Countersunk screw 8 x
120 mm



99211.0818
Countersunk screw 8 x
180 mm

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .