

Post bases 10529.1490



Technical data

Upper part dimensions	Ø 96 x 8 mm
Upper part holes	4 St. Ø 10,5 mm
Lower part dimensions	160 x 100 x 8 mm
Lower part holes	4 St. Ø 13 mm
Lower part thread	M24 x 250 mm
Adjustment range	303 - 418 mm
Max. characteristic load-bearing capacity in compression/tension for steel	74,0* / 36,9* kN
Max. characteristic load-bearing capacity in compression/tension for timber	152,0 / 50,0 kN


Post bases, Plug-in system Z Turn – Click, the new innovative post base system. With few handlings, without time-consuming and inconvenient screwing the new plug-in system allows an efficient solution of assembly. Maximal load capacities in compression, traction and horizontal stresses are guaranteed through the optimal material thickness of the post base. A height adjustment is possible even when mounted and under heavy load.

Post bases 10529.1490

Accessoires



50934.2000
Grooving cutter Ø 20 mm



58000.0000
Milling and assembly
template for connectors
88004 - 88322



58000.1100
Milling template for FM8 Ø
100 mm

Post bases 10529.1490



99110.1012

Washer-head screw 10 x
120 mm Stainless steel



99210.1012



99210.1016

Washer-head screw 10 x
160 mm