

Post bases 10952.1000




Technical data

Hole Ø 12 mm at top	4
Installation height mm	146 - 211
Bottom plate mm	160 x 100 x 8
M 24 thread at the bottom	65
M 24 thread at the top	65
Bore Ø 13 mm at the bottom	4
Upper plate mm	Ø 100 x 8
Max. characteristic load-bearing capacity in compression/tension for steel	83,8* / 11,8* kN
Max. characteristic load-bearing capacity in compression/tension for timber	90,0 / 50,0 kN

A system for all applications! Threads of 20 to 30 mm and the most varied plate sizes with 6 to 15 mm material thickness - we have the perfect solution for any application. Lift-off and lateral impacts can be counteracted with a straight screw connection into the cross-grained wood using fully-threaded 10 x 120 mm wood screws (with European Technical Approval) or a strut or lateral latches. Of course, post bases of the right/left-threaded system are still height-adjustable when mounted and under heavy load. The use of additional lock nuts increases the rigidity of the connection. For lateral fixation, the mandrel M24 x 110 mm is inserted into the timber column.

Post bases 10952.1000

Accessoires

**50020.2400**

Drill jig for precise
guidance of the drill bit Ø
24 mm

**99110.1012**

Washer-head screw 10 x
120 mm Stainless steel