

Post bases 10930.9000



Technical data

Installation height mm	168 - 283
Bottom plate mm	140 x 189 x 6
M 24 thread at the bottom	65
M 24 thread at the top	150
Upper plate mm	Ø 100 x 8
Bottom hole: 11 x 60 mm slotted hole	4
Top hole	4x Ø 12 mm

To simplify assembly still further, we have developed the 10930 item range. The upper parts have a tube diameter of 42.4 mm. They are simply inserted into the wood post and fastened with 4 fully-threaded Ø 10 x 120 mm wood screws. This saves you valuable assembly time while providing the typical values regarding compressive, tensile and transverse forces, and you can still continue to use our wood twist drill bit or your joinery machine to make the required borehole in the support. The upper part makes for an exceptionally wide adjustment range in the post bases of the 10930 / 10931 series. Of course, the upper part can also be used as a post-purlin connection. A versatile and combinable support foot, which remains height-adjustable even when mounted and under heavy load. The use of additional lock nuts increases the rigidity of the connection. We offer the manufacturing industries of screw-in foundations the opportunity to execute timber connections with high-quality post bases. The PTP-Series is designed to absorb vertical and horizontal stresses as well as lift-off forces. A height adjustment is possible even when mounted and under heavy load.