

Post bases 10921.1104




Technical data

Upper part dimensions	Ø 100 x 6 mm
Upper part holes	4 x Ø12 mm
Upper part thread	M24 x 85 mm
Lower part dimensions	100 x 100 x 6 mm
Lower part holes	4 x Ø13 mm
Lower part thread	M24 x 90 mm
Adjustment range	190 - 255 mm
Max. characteristic load-bearing capacity in compression/tension for steel	90,2* / 7,4* kN
Max. characteristic load-bearing capacity in compression/tension for timber	120,0 / 50,0 kN

A system for all applications! Threads of 20 to 30 mm and the most varied plate sizes with 6 to 15 mm material thickness - we have the perfect solution for any application. Lift-off and lateral impacts can be counteracted with a straight screw connection into the cross-grained wood using fully-threaded 10 x 120 mm wood screws (with European Technical Approval) or a strut or lateral latches. Of course, post bases of the right/left-threaded system are still height-adjustable when mounted and under heavy load. The use of additional lock nuts increases the rigidity of the connection.

Post bases 10921.1104

Accessoires




50020.2400

Drill jig for precise
guidance of the drill bit Ø
24 mm



50934.2000

Grooving cutter Ø 20 mm



58000.0000

Milling and assembly
template for connectors
88004 - 88322



58000.1100

Milling template for FM8 Ø
100 mm