

Connectors 88107.1000



Technical data

Dimensions W x H x D (mm)	40 x 70 x 12
Number of screws	10
Usable screw size	Ø4,5 x 50 - 80 mm
Minimum timber dimensions with screws Ø4,5x50 mm on the secondary beam	50** x 80 mm
Minimum timber dimensions with screws Ø4,5x50mm on the main beam	60 x 80 mm
Characteristic load-bearing capacity* in the insertion direction with screws Ø4,5x50 mm	7,18 kN
Characteristic load-bearing capacity* in the insertion direction with screws Ø4,5x80 mm	11,46 kN
VPE	10

Optimal distances to the edges and variable screws length ensure accuracy of fit for each timber section.

* Further static values can be found in our statics book or the ETA 15/0187.

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA 15/0187.

Connectors 88107.1000

Static values

Effektive Gewindelänge (l_{ef})		Mindestquerschnitt (mm)				Charakteristische Tragfähigkeit R_k (kN)									
						Vollholz C24 ($\rho_k = 350 \text{ kg/m}^3$)					Brettschichtholz GL24h ($\rho_k = 385 \text{ kg/m}^3$)				
		HT		NT				NT		HT			NT		HT
Schrauben	l_{ef} (mm)	Höhe	Breite	Höhe	Breite	$F_{2,Rk}$	$F_{3,Rk}$	$F_{4,Rk}$	$F_{4,Rk}$	$F_{1,Rk}$	$F_{2,Rk}$	$F_{3,Rk}$	$F_{4,Rk}$	$F_{4,Rk}$	$F_{1,Rk}$
4,5x50 mm	44 mm	80	60	80	50	6,65	6,26	6,26	9,89	6,01	7,18	6,56	6,56	10,38	6,49
4,5x60 mm	54 mm	90	70	90	50	8,00	6,26	6,26	9,89	7,23	8,63	6,56	6,56	10,38	7,80
4,5x80 mm	74 mm	110	90	110	50	10,62	6,26	6,26	9,89	9,59	11,46	6,56	6,56	10,38	10,35

* Further static values can be found in our statics book or the ETA 15/0187.


** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA 15/0187.

Connectors 88107.1000

Accessoires



50934.1000
Grooving cutter Ø 10 mm




58000.0000
Milling and assembly
template for connectors
88004 - 88322



58396.0000
Collet holder



58396.0008
Collet Ø 8 mm



58399.0000
Milling unit composed of
Milling bit, milling template
and hand overhead...



99111.4550
Countersunk screw V2A
4,5 x 50 mm



99111.4560
Countersunk screw V2A
4,5 x 60 mm

* Further static values can be found in our statics book or the ETA 15/0187.

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA 15/0187.