

Tools 55890.0000



Technical data

Designation	PowerClamp III D40/90
Drill hole diameter (mm)	40
Max. load capacity	bis 1.500 kg
Weight	Je Klemme 1,8 kg

Lifting clamp PowerClamp III D40/90 The lifting clamps - the latest innovation in timber construction. Enables you easily to raise wooden beams and massive edge glued panels through a simple and quick fastening of the lifting clamps. Depending on the demand the D40/90 is appropriate for a load carrying capacity up to 1500 kg, the D25/70 for a load carrying capacity up to 500 kg. Drill, apply, lift! Advantages of PowerClamp - Major time savings - No other lifting gear needed - No damage of wood surface - No soiling - RFID-Transponder for digital recording and theft protection (D40/90) Scope of supply - 2x PowerClamp (D40/90) - 1x Drill (40 mm) - 1x High quality transport box The low-maintenance lifting clamp is your optimal partner for each construction project. Despite the low weight it is extremely robust.

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .



Innovative wood connection systems
for the highest demands

Tools 55890.0000

Static values

In contrast to fasteners, which can either be calculated according to a valid norm or must have a technical approval, lifting equipment requires a declaration of conformity.

This is included in the operating instructions.

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .




Pitzl Metallbau GmbH & Co. KG
Siemensstraße 26
D-84051 Altheim

Tel.: +49 (0) 8703 9346-0
E-Mail: info@pitzl-connectors.com
Web: www.pitzl-connectors.com

Tools 55890.0000

Accessoires



55895.0000

Spacer for PowerClamp III
D40/90

* Further static values can be found in our statics book or the ETA .

** Steel failure decisive Values in brackets for service class 3* Further static values can be found in our structural analysis book or the ETA .